

Press Release 17/2013

Neustadt-Fernthal, August 22, 2013

The New BOY 25 E is even more powerful

In a few weeks, the new BOY 25 E with 250 kN clamping force will be presented to the public for the first time at K 2013 in Dusseldorf (hall 13 / booth A 43). According to the well known compactness of all BOY injection moulding machines, a footprint of only 1,8 m² is required. When constructing we also paid attention to the improvement of the accessibility to the mould space and the plasticizing units. This set the preconditions for an even faster mould change. Thanks to the servo-motor pump drive not only the energy costs can be kept low, but also a reduction of the oil amount to 65 liters and a clearly reduction of the noise emission to below 67 dB (A) were realized.

In the area of the mould space and the trip chute, smoother surfaces ensure a safe removal of the parts and improved clean room compatibility.

The new model has six optional injection units in the range of the Euromap sizes SP 11 to SP 82. With the availability of screw diameters from 12 mm to 32 mm (for 4,5 to maximum 76,4 cm³ stroke volume) an enormous scope of applications is covered.

As a special highlight, differential injection is possible with the thermoplastic plasticizing units SP 11, SP 16 and SP 39.

“With the new differential injection units, we provide the user maximum flexibility“ Martin Kaiser, BOY Head of Mech.-Hydr. Design, stated. “Especially the injection unit SP 39 with

the 18mm and 22 mm screw diameters will be probably most in demand, since the differential injection can be optionally switched on or off,” explains Kaiser. In this way the user can optimally adapt the injection unit to the mould: on the one hand fast injection for thin walled parts or on the other hand very high injection pressures for difficult to fill form geometries. This flexibility is possible through loading in terms of software of the constant lists, which are valid for the respective screw diameter and which determine the performance of the injection units.

Additional advantages of the differential injection units are shorter cycle times as well as the reduction of time-consuming and costly alterations. “Loading of the respective constant lists is in any case faster than a mechanical alteration,” states the BOY Head of Design.

With the newly developed BOY 25 E and the flexible differential injection units, BOY demonstrates again its efforts to make the injection moulding machines even more flexible and efficient in the terms of the user.



Company profile

Dr. Boy GmbH & Co. KG is one of the leading worldwide manufacturers of injection moulding machines with clamping forces below 1,000 kN. The very compact, durable machines work precise, energy-saving and therefore highly economical. BOY continually sets new standards in our industry with innovative concepts and solutions.

Since the company was founded in 1968, over 40,000 injection-moulding machines have been delivered worldwide. The privately owned company continues to put special emphasis on engineered performance and high-class "made in Germany" workmanship.

For further information visit <http://www.dr-boy.de/>.

Photo(s): > BOY 25 E with Procan ALPHA[®] 2 control

Words: 443

Lines: 41

Characters: 2.592

Your contact person:

Thomas Breiden
Head of Marketing
Dr. Boy GmbH & Co. KG
Neschener Straße 6
53577 Neustadt-Fernthal
Germany

Phone: (+49) 2683 / 307-0

Fax: (+49) 2683 / 32771

E-Mail: th.breiden@dr-boy.de

Internet: www.dr-boy.de

A request:

The colour scheme of the BOY injection moulding machines differs from those of other manufacturers. We are therefore keen to make the differences clear in our pictures. The



colour of the typical "BOY blue" differs from a common green or blue. If you can influence the colour reproduction in your magazine, please use the following definitions:

Four-colour definition (CMYK) : 100 % C / 0 % M / 25 % Y / 40 % K
or Pantone 3155 or RAL 210 40 35.

Thank you very much in advance.